

ASTM A252 (PLAIN END) PILING PIPES

Outside Diameter		Wall Thickness		Nominal Weight		Outside Diameter		Wall Thickness		Nominal Weight		Outside Diameter		Wall Thickness		Nominal Weight	
inch	mm	inch	mm	lb/ft	kg/m	inch	mm	inch	mm	lb/ft	kg/m	inch	mm	inch	mm	lb/ft	kg/m
6	152.4	0.134	3.4	8.40	12.50	12	304.8	0.134	3.4	15.21	22.63	14	355.6	0.469	11.9	67.84	100.96
		0.141	3.6	8.83	13.14			0.141	3.6	15.99	23.80			0.500	12.7	72.16	107.38
		0.156	4.0	9.75	14.50			0.150	3.8	17.00	25.29	16	406.4	0.134	3.4	22.73	33.82
		0.164	4.2	10.23	15.23			0.164	4.2	18.56	27.62			0.141	3.6	23.90	35.57
		0.172	4.4	10.72	15.95			0.172	4.4	19.45	28.94			0.150	3.8	25.42	37.82
8	203.2	0.141	3.6	11.85	17.63			0.179	4.5	20.23	30.10			0.164	4.2	27.76	41.32
		0.172	4.4	14.39	21.42			0.188	4.8	21.23	31.59			0.172	4.4	29.10	43.31
8-5/8	219.1	0.141	3.6	12.79	19.03			0.203	5.2	22.89	34.06			0.179	4.5	30.27	45.05
		0.172	4.4	15.54	23.13			0.219	5.6	24.65	36.69			0.188	4.8	31.78	47.29
		0.188	4.8	16.96	25.23			0.230	5.8	25.87	38.49			0.203	5.2	34.28	51.02
		0.203	5.2	18.28	27.20	0.250	6.4	28.06	41.76	0.219	5.6	36.95	54.98				
		0.219	5.6	19.68	29.29	0.281	7.1	31.45	46.80	0.230	5.8	38.77	57.70				
		0.250	6.4	22.38	33.31	0.312	7.9	34.81	51.81	0.250	6.4	42.09	62.64				
		0.277	7.0	24.72	36.79	12-3/4	323.9	0.134	3.4	18.07	26.89	0.281	7.1	47.22	70.27		
		0.312	7.9	27.73	41.26			0.141	3.6	19.01	28.28	0.312	7.9	52.32	77.87		
		0.322	8.2	28.58	42.53			0.150	3.8	20.20	30.07	0.344	8.7	57.57	85.68		
		0.344	8.7	30.45	45.32			0.164	4.2	22.07	32.84	0.375	9.5	62.64	93.22		
		0.375	9.5	33.07	49.22			0.172	4.4	23.13	34.42	0.438	11.1	72.86	108.44		
		0.438	11.1	38.33	57.05			0.179	4.5	24.05	35.80	0.469	11.9	77.87	115.88		
0.500	12.7	43.43	64.63	0.188	4.8			25.25	37.57	0.500	12.7	82.85	123.29				
10	254.0	0.134	3.4	14.13	21.03			0.203	5.2	27.23	40.52	18	457.2	0.141	3.6	26.92	40.06
		0.141	3.6	14.86	22.12			0.219	5.6	29.34	43.66			0.172	4.4	32.78	48.78
		0.150	3.8	15.79	23.51			0.230	5.8	30.78	45.81			0.188	4.8	35.80	53.27
		0.164	4.2	17.24	25.66	0.250	6.4	33.41	49.71	0.219	5.6			41.63	61.95		
		0.172	4.4	18.07	26.89	0.281	7.1	37.46	55.74	0.230	5.8			43.69	65.02		
		0.179	4.5	18.79	27.97	0.312	7.9	41.48	61.74	0.250	6.4			47.44	70.60		
		0.188	4.8	19.72	29.35	0.330	8.4	43.81	65.20	0.281	7.1			53.23	79.21		
		0.203	5.2	21.26	31.64	0.344	8.7	45.62	67.89	0.312	7.9			58.99	87.79		
		0.219	5.6	22.90	34.08	0.375	9.5	49.61	73.83	0.344	8.7			64.93	96.62		
		0.230	5.8	24.02	35.75	0.438	11.1	57.65	85.79	0.375	9.5			70.65	105.15		
0.250	6.4	26.06	38.78	0.500	12.7	65.48	97.44	0.438	11.1	82.23	122.37						
10-3/4	273.1	0.134	3.4	15.21	22.63	14	355.6	0.134	3.4	19.86	29.56	20	508.0	0.141	3.6	29.93	44.55
		0.141	3.6	15.99	23.80			0.141	3.6	20.89	31.09			0.150	3.8	31.83	47.37
		0.150	3.8	17.00	25.29			0.150	3.8	22.21	33.05			0.164	4.2	34.78	51.76
		0.164	4.2	18.56	27.62			0.164	4.2	24.26	36.10			0.172	4.4	37.84	57.16
		0.172	4.4	19.45	28.94			0.172	4.4	25.43	37.84			0.179	4.5	39.36	58.26
		0.179	4.5	20.23	30.10			0.179	4.5	26.45	39.36			0.188	4.8	41.31	61.16
		0.188	4.8	21.23	31.59			0.188	4.8	27.76	41.31			0.203	5.2	44.56	65.82
		0.203	5.2	22.89	34.06			0.203	5.2	29.94	44.56			0.219	5.6	48.01	70.85
		0.219	5.6	24.65	36.69			0.219	5.6	32.26	48.01			0.230	5.8	50.38	74.55
		0.230	5.8	25.87	38.49			0.230	5.8	33.86	50.38			0.250	6.4	54.69	80.15
		0.250	6.4	28.06	41.76			0.250	6.4	36.75	54.69	0.281	7.1	61.33	90.15		
		0.279	7.1	31.23	46.48			0.281	7.1	41.21	61.33	0.312	7.9	67.94	100.15		
		0.307	7.8	34.27	51.00			0.312	7.9	45.65	67.94	0.344	8.7	74.73	110.15		
		0.344	8.7	38.27	56.95			0.344	8.7	50.22	74.73	0.375	9.5	81.28	120.15		
		0.365	9.3	40.52	60.30			0.375	9.5	54.62	81.28	0.438	11.1	94.50	139.20		
0.438	11.1	48.28	71.85	0.438	11.1	63.50	94.50	0.469	11.9	104.23	155.12						
0.500	12.7	54.79	81.53					0.500	12.7	115.88	171.15						